

Blue fields must be completely filled in to get an offer. Fill in remaining data if the information is available.

NOTE! Unanswered option question is taken as not selected.

General Data	Purchase number:			Document language: Packing type:
	Commission number:			
	Contact person/company:			
	Tel, Fax, E-mail:			
	Requested delivery date:			
	Site address city/country:			
	Site address street:			
	Delivery address:			
Delivery zip. city, country:				

Cylinder	Lift system:		Product:	
	Empty car pressure / Car weight:	bar / kg	Static full load:	bar
	Rated load:	kg	Rated speed:	m/s
	Cylinder:	type:	qty:	
	Piston diameter:	cyl 1: mm	cyl 2:	mm
	Piston diameter 2:	cyl 1: mm	cyl 2:	mm
	Piston diameter 3:	cyl 1: mm	cyl 2:	mm
	Piston diameter 4:	cyl 1: mm	cyl 2:	mm

Hydraulic data	Power unit	Pump flow (Veni 50Hz, vidi 70Hz):	l/min	Other:	l/min	Existing pump flow:	l/min
		Motor:	kW	Other:	kW	Existing motor size:	kW
		Inverter:	kW	Other:	kW	Existing inverter:	kW
		Tank:	l	Other:	l	Existing tank:	l
		Pump (Vidi):	l/min	Tank color:		Oil spillage tray:	☐
		Hose connection:		New hose:	m	Hose coupling:	☐
		Supply voltage:	V	Isolation transformer:	☐ (if necessary to neutral zero from PE)		
		New rated speed:	☐ Up: m/s	☐ Down: m/s			
		Options:	☐ Max pressure switch, DZE ☐ Oil level switch ☐ Full load pressure switch, DZE ☐ External oil level indicator ☐ Min. pressure switch ☐ Connection for oil cooler ☐ Tank heater w. thermostat ☐ Supply for oil cooler				
		Hydraulic oil:	☐ pcs, 20 l can	☐ ECO oil	5 l Anti stick-slip additive (min 2%)		

Lift/building	Travel height (LH) [1000-30000 mm]:	mm
	Motor room Floor:	Distance Shaft - Motor room: mm
	Standard addition is 5m for horiz. measures in shaft and motor room.	Extra addition: mm
	Short distance?(<460 mm) ☐ Yes Distance: mm	Floors:
	LSF Cables: ☐ Yes Separate control cabinet: ☐ Yes	

Alarm tele-phone	Delivery by Hydroware:		Existing:	
	☐ Safeline Intercom	☐ Intercom		

Data Schematics	Floors and door drive	No. of floors [2-16]: pcs	No. of landing doors: pcs	No. of access sides: pcs
		Access side 1 Floor: ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6 ☐ 7 ☐ 8 ☐ 9 ☐ 10 ☐ 11 ☐ 12 ☐ 13 ☐ 14 ☐ 15 ☐ 16		
		Access side 2 Floor: ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6 ☐ 7 ☐ 8 ☐ 9 ☐ 10 ☐ 11 ☐ 12 ☐ 13 ☐ 14 ☐ 15 ☐ 16		
		Access side 3 Floor: ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6 ☐ 7 ☐ 8 ☐ 9 ☐ 10 ☐ 11 ☐ 12 ☐ 13 ☐ 14 ☐ 15 ☐ 16		
		Access side 1	Door drive side 1	Other:
		Access side 2	Door drive side 2	Other:
		Access side 3	Door drive side 3	Other:

Car door EN81-20

Automatic Door	Door reversal 1:		Voltage:	☐ 24 VDC	☐ 230 VAC	☐	Output:	
	Door reversal 2:		Voltage:	☐ 24 VDC	☐ 230 VAC	☐	Output:	
	Door reversal 3:		Voltage:	☐ 24 VDC	☐ 230 VAC	☐	Output:	
Swing door	Swing door opener:		Phase:	☐ 1~	☐ 3~	Location:	☐ Car	☐ Landing door
	Light curtain:		Other:		Voltage:		Output:	
	Retracting ramp, voltage:		Options:	☐ Safety sill	☐ Roof flap			
LOP/LIP	Push buttons:	☐ Schaefer	☐ Digisign	☐ Kinds	☐ MX-Basic	☐ DMG	Other:	
	Floor indicators:		Other:		Code:		Location:	
	Options:	☐ Acc. to Appendix G	☐ Send button	☐ "Door open" button	☐ Occupied indicator, at direct control	☐ Car here indicator	☐ Arrival signal (Gong)	☐ Out of service switch
COP/CIP	Number of COP's		Push buttons:	☐ Schaefer	☐ Digisign	☐ Kinds	☐ MX-Basic	☐ DMG
	Floor indicators:		Other:		Code:		Location:	
	Options:	☐ Acc. to Appendix G	☐ Stop button	☐ Open button	☐ Close button	☐ Fan	☐ Overload indicator	☐ Travel direction arrows, type:
Data Schematics	Key switches:	☐		☐		☐		
	Voice annunciator:		Other:					
	Voice message:							
Safety	Protection against free fall and sinking:	☐ Pawl device	Voltage:		Qty:		☐ Not retract	☐ Buffer
		☐ Safety gear	Slack rope:		☐ Tension weight switch (OSG)	☐ With anti-creep	☐ Test & Reset	
		☐ OSG:	Voltage:		☐ One way restrictor:	☐ Valve UCM/A3		
Safety	Rupture valve:	☐ Delivered by Hydroware	☐ Existing					
	Extra safety:	☐ Low pit	☐ Low top	☐ EN 81-21	☐ EPR 130	☐ Pit prop, service		
		☐ Existing extra final limit switch in headroom for low top (inspection travel)	☐ Extra final limit switch deliv. by Hydroware	Prop, low pit:		Prop, low top:		
Control	Extra door contact (low pit / low top):	☐ Monostable	☐ Bistable	Reset voltage:		Location:		☐ Hidden swing door contact
	Options:	☐ Top runby buffer, quantity:		☐ Trap door on car roof				
	Emergency stop:	Pit (2 acces sides at bottom floor = 2; otherwise 1)	qty:		Car roof(2 access sides, >1m to door = 2; otherwise 1)	qty:		
Others	Lifts in group:	☐ 2	☐ 3					
	Control system:		Return floor:		After time:		min	
	Options:	☐ Fire recall	Power supply of fan:		Installation handle:			
Others	Shaft light:	☐ New deliv. by Hydroware	☐ Control	☐ Power supply	☐ Car top control (BS7255)			
	Notes/							
	Other functions:							